



QRD1000ProID10



QRD1000ProID20



QRD1000ProID30



QRD1000ProID40

## QRD1000ProID

### RFID wiegand readers

The QRD1000ProID series of wiegand readers offer different reading technologies such as 125KHz EM, 13.56MHz Mifare®, DESFire®, FeliCa or Legic. With robust all-weather protection, a modern aesthetic design, different sizes and versions with and without keypad, they are the best choice for indoor and outdoor applications.

#### Technical specifications

<b>Reading range</b>	QRD1000ProID10 EM/IC 3,5cm. QRD1000ProID20/ 30/ 40 EM/ IC 5cm	<b>Protection</b>	IP65
<b>Reading time</b>	300 ms	<b>Material</b>	ABS+PC
<b>Port of entry</b>	External LED control External Buzzer Control	<b>Feeding</b>	Operating voltage 7~13V DC
<b>Output format</b>	Wiegand 26 or 34 Bits adjustable	<b>Temperature</b>	-20 °C to 65 °C
<b>LED</b>	White flashing led for standby Red and green LEDs	<b>Humidity</b>	10% ~ 90% relative humidity no condensed
<b>Audio</b>	Beep	<b>Dimensions</b>	QRD1000ProID10: 80.5 × 44 × 15mm. QRD1000ProID20/30: 90 × 90 × 16mm. QRD1000ProID40: 116 × 75 × 15mm.

