



Qualica-RD ANDROMEDA 50

Qualica-RD's new customizable tripod turnstile for tight spaces.

Qualica-RD ANDROMEDA 50. Bidirectional or unidirectional tripod turnstile. IP65 watertightness level, for indoor/outdoor use. Fire safety requirements; arms drop automatically. Green and red LED pictogram indicator for passage status.


Color and dimensions can be customized, depending on the installation environment. Logo can be customized.

3-year warranty. Easy to install and maintain. Low noise level, the system operates smoothly. Low power consumption.



QUALICA-RD

ANDROMEDA50 Tripod









Card Reader

QR Code Reader

Biometric Readers

Technical specifications

Certifications	Compliance CE, ROHS, FCC
Framework Material	Steel / White and black stoving varnish / Tempered glass
Arm material	Stainless Steel
Dimensions	380 * 280 * 1000mm
Net Weight	35kg/pcs
Passage Width	550mm
Passing Direction	Single directional and Bi-directional
MCBF	10 million
Power Supply	AC220V/110V, 50/60Hz
Operation Voltage	24V DC
Power Consumption	40W
Operation Temperature	-20 °C - 75 °C
Operation Humidity	0 ~ 95% (No freeze)
Working Environment	Indoor / Outdoor
Flow Rate	40 people per minute
LED Indicator	Two LED indicators on top
Communication	Dry contact, Relay signal, RS485
Emergency	Arms will drop down automatically
Flexibility	Integrate with any access control

Dimensions (mm)

