



Qualica-RD ANDROMEDA 70

Fast opening speed of 0.1sec. 55 persons/min.

Qualica-RD ANDROMEDA 70. The perfect turnstile for sites with a high flow of visitors. 55 people per minute. Supports 600mm-1100mm for wide step, wheelchairs, baby carriages, etc. Indoor use. Green and red LED pictograms for passage status.

The width and height of the arm glass are optional. Color can be customized. Customized logo on glass sheets. Optional number of infrared sensors. Optional waterproof.

3-year warranty. Easy to install and maintain. Low noise level. Low energy consumption. Fire safety requirements; arms open automatically.



ANDROMEDA70 Turnstile





Technical specifications

| Material | Steel / White and black stoving varnish / Tempered glass |
|-----------------------|--|
| Arm material | Plexiglas - transparency |
| Dimensions | 1400 * 120 * 978 mm |
| Net weight | 75kg/pcs (single core), 95kg/pcs (double core) |
| Passage width | 600mm (standard), 1100mm max. (handicap) |
| Arm height | 900mm (standard), 1800mm max. (optional) |
| Passing direction | Single directional and Bi-directional |
| MCBF | 15 million |
| Power supply | AC220V/110V, 50/60 Hz |
| Operating voltage | 24V DC |
| Power consumption | 40W |
| Operating temperature | -20 °C - 75 °C |
| Operating humidity | 0 ~ 95% (no freeze) |
| Working environment | Indoor / Outdoor (shelter) |
| Flow rate | 55 people per minute |
| LED indicator | Two LED indicators on top |
| Infrared sensor | 16 sensors (optional) |
| Comunication | Dry contact, Relay signal, RS485 |
| Flexibility | Integrate with any access control |

Dimensions (mm)



