



3-year  warranty



Biometrics



RFID



Barcode



QR Code

## Qualica-RD **CANOPUS PORTABLE**

Portable tripod not fixed or anchored to the ground, to be placed wherever necessary.

**Qualica-RD CANOPUS PORTABLE.** This turnstile can be placed wherever pedestrian access control is needed. Composed of tripod + base + railing and with wheels. Intelligent soft braking system

The top cover is made of black Plexiglas and the magnetic card panel is incorporated into the traditional stainless steel design. The entire body is made of stainless steel and is surrounded by a decorative LED light bar.

**3-year warranty.** Ideal for various scenarios such as exhibitions, lawns, gardens, construction sites, etc., as it allows easy mobility and use without the need to fix it to the ground with bolts.



QUALICA-RD

# CANOPUS Portable Tripod

## Features

- It is ideal for both indoor and outdoor use.
- In case of emergency, the tripod arms lower automatically to allow free passage.
- The whole system operates with low noise and no mechanical impact.
- Automatic reset function: the turnstile arm will automatically lock within 5 seconds.
- It has standard relay signal, which can integrate with any kind of third party access control system.



## Technical specifications

<b>Certification</b>	Conformity CE, ROHS, FCC
<b>Communication</b>	Dry contact, relay signal, RS485
<b>Frame material</b>	304 / 316 stainless steel (optional) + high-end black plexiglass
<b>Arm material</b>	304 / 316 stainless steel (optional) + (optional black rubber protector)
<b>Dimensions</b>	Turnstile: 360 * 260 * 980mm / Base: 980 * 720 * 50mm / Bar: 460 * 969mm
<b>Net weight</b>	50kg/unit
<b>Pitch width</b>	550mm (Arm length: 500mm)
<b>Pitch direction</b>	Unidirectional and Bidirectional
<b>MCBF</b>	10 million
<b>Power supply</b>	AC220V/110V, 50/60Hz
<b>Operating voltage</b>	24V DC
<b>Power consumption</b>	20W
<b>Operating temperature</b>	-20 °C - 75 °C
<b>Operating humidity</b>	0 ~ 95% (no freezing)
<b>Operating environment</b>	Indoor / Outdoor
<b>Flow rate</b>	35 persons per minute
<b>LED indicator</b>	Single blue LED strip (front+ top+ side)
<b>Emergency</b>	Arms lower automatically
<b>Flexibility</b>	Integrates with any access control



## Dimensions (mm)

