



Qualica-RD NAOS

Long-life performance, high operational reliability and fast response.

Qualica-RD NAOS. Speed turnstile with transparent plexiglass sheets (tempered glass optional), which can be raised to 900-1800mm (max). The passage width can reach 550-900mm, which is suitable for wheelchair users, baby strollers or pedestrians with bulky luggage.

The body is made of brushed stainless steel which is sturdy, rigid, rustproof, waterproof and durable. Ideal for both indoor and outdoor use.

3 years warranty. Suitable for offices, government buildings, banks, airports, stadiums, schools, hospitals etc.



NAOS Turnstile

Features

- A choice of one-way or two-way is available.
- It has a standard relay signal, which can be integrated with any type of access control system. (RFID, fingerprint and biometric reading device).
- In case of an emergency, the turnstile will automatically open to allow free passage when it is turned off.
- Infrared sensor alarm functions, in case of illegal intrusion and reverse intrusion. Anti-intrusion function.
- The whole system operates smoothly, with low noise and without mechanical impact.



Technical specifications

Frame material	304 / 316 stainless steel (optional) + tempered glass on the side
Arm material	Transparent Plexiglas / tempered glass (optional)
Dimensions and Weight	1440 * 192 * 1000mm / 75 kg/unit (single core), 85 kg/unit (double core)
Passage width	550 mm (standard), 900 mm (special passage)
Sheets height	900-1800mm (optional)
Passage direction	Unidirectional / Bidirectional
MCBF	10 million
Power Supply	AC220V/110V, 50/60Hz
Operating voltage	24V DC
Power consumption	40W
Operating temperature	-20 °C to 75 °C
Operation Humidity	0 ~ 95% (no freezing)
Flow rate	40-45 persons per minute
LED indicator	LED indicators on top
Infrared sensor	12 sensors (standard)
Emergency	Automatic sheets open when switched off
Communication	Dry contact, relay signal, RS485

Dimensions (mm)

