



# Qualica-RD PEGASI

Turnstile for access control with different glass heights.

**Qualica-RD PEGASI.** The passage width can reach 600mm for normal passage, and it can support 900mm or 1200mm arm for wide passage; wheelchair and pedestrians with large luggage can also pass.

The glass arm can be raised 900mm to 1800mm for high security control. Brushed stainless steel body, sturdy, anti-rust, waterproof and durable. The opening speed is 0.2 seconds.

3-year warranty. Ideal for areas where aesthetics are required; hotels, buildings, libraries, cinemas, gymnasiums, etc.

#### QUALICA-RD

## **PEGASI Speed Turnstile**

#### **Features**

- It is ideal for both indoor and outdoor use.
- Single or bi-directional direction can be selected.
- Automatic reset function: the turnstile arm will automatically lock within 5 sec (can be adjusted) if the passenger delay is given to the entrance.
- Integrate with RFID, fingerprint and biometric reading device.
- In case of emergency, the arms will open automatically to allow free passage when power off.



### Technical Specifications

Frame material	304 stainless steel
Arm material	tempered glass
Dimensions and Weight	1605 * 127 * 1000mm / 75kg/pcs
Pitch width	600-1200mm (one step)
Arm height	900-1800mm (max.)
Pitch direction	Monodirectional and bidirectional
MCBF	15 million
Power Supply	AC220V/110V, 50/60Hz
Operating voltage	24V DC
Power consumption	40W
Operating temperature	-15 °C - 60 °C
Operating humidity	0 ~ 95% (no freezing)
Operating environment	Indoor / Outdoor
Flow rate	50-55 persons per minute
Indicator	Yes
Infrared sensor	16 pairs
Emergency	Automatic arm opening when power is disconnected
Communication	Dry contact, relay signal, RS485

#### Dimensions (mm)





