



Biometrics



RFID



Barcode



QR Code

3 years **warranty**

Qualica-RD **CANOPUS 55**

Bidirectional tripod for access control.

Qualica-RD CANOPUS 55 is a quiet and compact bi-directional tripod. It has long-life performance, high operating reliability and fast response. The whole system operates smoothly, with low noise and no mechanical impact.

With emergency opening, automatic reset function and LED indicators. The body is made of brushed stainless steel, anti-rust, waterproof and durable. Unidirectional or bidirectional can be chosen.

3 years warranty. Ideal for hotels, gymnasiums, buildings, shopping malls, supermarkets, reception areas, libraries etc.



CANOPUS 55 Bidirectional Tripod


Features

- It is ideal for both indoor and outdoor use.
- In case of emergency, the tripod arms lower automatically to allow free passage.
- The whole system operates with low noise and no mechanical impact.
- Automatic reset function: the turnstile arm will automatically lock within 5 seconds.
- It has standard relay signal, which can integrate with any kind of third party access control system.




Technical specifications


Communication	Dry contact, relay signal, RS485
Body material	304 / 316 stainless steel (optional)
Arm material	304 / 316 stainless steel (optional) (black rubber protector)
Dimensions	480 * 280 * 1010mm
Net weight	45kg/unit
Pitch width	550mm (Arm length: 500mm)
Pitch direction	Unidirectional and Bidirectional
MCBF	10 million
Power supply	AC220V/110V, 50/60Hz
Operating voltage	24V DC
Power consumption	20W
Operating temperature	-15 °C to 60 °C
Operating humidity	0 ~ 95% (no freezing)
Operating environment	Indoor / Outdoor
Flow rate	35 persons per minute
LED indicator	Two LED indicators on the top, front and black side
Emergency	Arms lower automatically
Flexibility	Integrates with any access control




Dimensions (mm)



Side View



Top View



Front View

