



3 years warranty



Remote
Control



Button
contactless



Card
Reader



QR Code
Reader



Fingerprint
Reader



Facial
Reader



Hand Palm
Reader

Qualica-RD 403

Motorized steel and plexiglass revolving turnstile for access control

The revolving door **Qualica-RD 403** has transparent plexiglass panels, 3-wing 3-leaf, high quality bi-directional motor and long service life. The body material 304 stainless steel body (316 as option). Dimensions can be customized to meet the customer's needs.

Color and logo are also customizable. Panel spacing is 120 degrees. In case of emergency, the door will open automatically to allow free passage when the power is cut off.

3 years warranty. Easy to install and maintain. It is specially designed for places such as office buildings, gymnasiums, banks, etc.



QRD-403 Motorized Revolving Door

Features

- The whole system runs smoothly, long-lasting performance, high operating reliability and fast response.
- The mechanism is equipped with a self-regulating hydraulic damping device.
- Support can be integrated with any kind of third party systems.
- Anti-pass back function: only one person passes at a time.
- Suitable for indoor/outdoor use.
- Automatic opening in case of power failure or fire.
- One-way and two-way operation.
- Free 3D mounting.



Technical specifications

Material of the structure	304 stainless steel (optional 316)
Dimensions	1406 * 1370 * 1050 mm
Arms	120 °C 3-section rotor
Net Weight	80kg / unit
Pitch Width	1 rail; 560 mm/rail
Pitch Direction	Unidirectional and Bidirectional
Lifetime (MCBF)	15 million
Power supply	AC220V/110V, 50/60Hz
Operating Voltage	24V DC
Power consumption	40W
Operating temperature	-15 °C to 60 °C
Operating humidity	0 ~ 95% (No freezing)
Operating environment	Indoor / Outdoor
Flow rate	30 persons per minute
Entrance	Dry contact
Emergency	Automatic opening of the arm in case of power failure
Communication	Dry contact, relay signal, RS485



Dimensions (mm)

