



Qualica-RD **ALHENA**

Sheets can be extended to a height of 1.8 meters for increased safety.

Qualica-RD ALHENA. Access control turnstile for pedestrian entry or exit in restricted areas and both directions. The opening and closing speed rate is very fast 0.2 seconds (adjustable).

The passage width reaches 600-1140mm, which is suitable for people with reduced mobility or pedestrians with bulky luggage. Brushed stainless steel body, robust, rustproof, waterproof and durable.

3-year warranty. It is ideal for areas with general pedestrian traffic; parks, schools, factories, libraries, cinemas, gymnasiums, etc.



QUALICA-RD

ALHENA Turnstile Speed Gate

Features

- It is ideal for both indoor and outdoor use.
- Long life performance and fast response.
- Automatic reset function: the turnstile will lock automatically within 5 sec. (can be set) if there is passenger delay at if the passenger delay is given at the entrance.
- Can integrate RFID, fingerprint and biometric reading device.
- In case of emergency, the turnstile will open automatically to allow free passage (counter-locking).



Technical specifications

Material of the structure	304 / 316 stainless steel (optional) + tempered glass on the side
Dimensions	1600 * 160 * 1000mm
Net weight	75kg/unit (single core), 85kg/unit (double core)
Pitch width	600mm(standard), 1140mm (wheelchair)
Height and material of sheets	900-1400mm (Max.) / transparent plexiglass (standard), tempered glass (optional)
Pitch direction	Unidirectional and Bidirectional
MCBF	15 million
Power supply	AC220V/110V, 50/60Hz
Operating voltage	24V DC
Power consumption	40W
Operating temperature	-20 °C to 75 °C
Operating humidity	0 ~ 95% (no freezing)
Operating environment	Indoor / Outdoor
Flow rate	40-45 persons per minute
LED indicator	LED indicators on top
Infrared sensor	12 sensore
Communication	Dry contact, relay signal, RS485

Dimensions (mm)

